


euku color oil FS



1 PRODUCT DESCRIPTION

Pigmented full solid impregnation based on natural oils. Solvent-free, easy to handle, sealable with strato waterbased lacquers, without layer buildup to get natural open pore characteristic.

Due to its high penetration it creates an especially hard-wearing floor.

abZ-Nr. Z-157.10-156

abZ-Nr. Z-157.10-157 (primer under 1K strato-lacquers)

abZ-Nr. Z-157.10-155 (primer under 2K strato-lacquers)

Color Shades:

Snow (White)	Coffee	Pine
Black	Hazel	Cherry
Light Grey	Mahogany	Red
	Ebony	

Please regard Color Shade Card.

2 AREAS OF APPLICATION

Oil for the colored impregnation of sanded wood, parquet and cork floors. Optionally for use with the reactive additive **euku master FS**. In that 2part application approved for use as colored primer (oil-stain) under strato waterbased lacquers (*).

3 APPLICATION


Apply **euku color oil FS** evenly with a spatula or squeegee. In the case of a highly absorbing wood, in order to avoid spatula marks, repeat the spatula application wet-in-wet, according to the absorbance of the wood. After 15-30 minutes massage the wet excess with a singledisc machine and pad, polishing away surplus from the surface until none remains. During application the oil must on no account be allowed to dry on the floor. A further polishing step with a polishing cloth underneath increases the gloss finish and ensures that there is no excess oil left.

- Pre-watering the floor is strongly recommended and improves color density and color evenness, hard-wearing and resistance properties (**).
- The professionally sanded and grouted subsurface must be in a clean, dry condition, free of oil, wax and dust.
- In the case of soft and tropical woods escaping resin can lead to delays in drying, or adversely affect visual appearance.
- In the case of insufficient grouting, rub away the oil pushing out of the joints with a green pad after 1 day.
- After full drying an application of **euku refresher** is possible, in order to even out any cloudy patches in the gloss, due to the differing absorbent behaviour of the wood.

4 CONSUMPTION

approx. 30-50 ml/m² (20-30 m²/l) for oak during the first application.

euku color oil FS



Higher consumption is possible in the case of coarse sanding, wider joints and highly absorbent wood, although subsequent applications will use considerably less.

5 DRYING TIME

Can be walked on carefully, or worked on again, after about 24 hours (at 23 °C, 50% relative humidity and air movement). The area should not be mopped wet in the first 7 days afterwards. After 10 days at the earliest carpets can be laid on the floor.

Low temperatures, increased humidity, poor ventilation and drying inhibiting wood ingredients can extend the drying time substantially.

The use of a ventilator is recommended to improve oil hardening.

6 CLEANING / CARE

Please note that the surface image of an oil-impregnated floor is only finalized after use, cleaning and care. After complete hardening, use **euku care emulsion** for cleaning and care and **euku refresher** for subsequent oil care. Please observe eukula care instructions for oil impregnated floors.

7 STORAGE

24 months in an unopened original canister. Remove any skin which may have formed before use. Store in a cool, dry place. Keep out of the reach of children.

8 TECHNICAL DATA

Contains substances: natural oils and waxes, modified vegetable oils, drying agents free of lead and cobalt.

voc (g/l) <1 / GISCODE: Ö10+ / 2004/42/IIA(f)(700)700

ADR/RID: not a dangerous good as defined by transport regulations.


GHS/CLP: The product is not classified according to the GHS/CLP regulation.

Even when using low-pollution products, the usual safety measures are to be observed. Keep out of the reach of children. Completely emptied canisters can be disposed of in domestic waste.

8 SPECIAL NOTES

- Warning! Danger of self-combustion of oil-soaked working materials, such as cloths, fleeces, sanding dust, etc. These should be enclosed in an air-tight metal container, or soaked with water and disposed of in a fire-safe way. The oil itself is not self-combusting.
- Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of a different batch, mix this in a separate container before using.
- It is recommended that a colour test is done on the same wood with the same sanding/working technique as the floor to be treated. The resulting colour can depend on it.

euku color oil FS



- Oiled surfaces smell. The smell diminishes with increasing drying in the course of days. In the initial time after an oil treatment ventilate the rooms well.
- Oiled surfaces and wood show specific discolorations due to light influence.
- (*) Please read the Technical Information „Notes on building up oil/waterbased lacquer“.
- (**) Please note the Technical Information „Why water before oiling?“.

9 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes
- Safety data sheet available on request.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage www.eukula.com or on request from the address quoted below.

eukula – We Care About Wood Floors

Headquarter CC-Dr. Schutz GmbH Holbeinstraße 17 D-53175 Bonn Tel.: + 49 228 / 95 35 2-40 Fax: + 49 228 / 95 35 2-46 E-Mail: export@dr-schutz.com www.dr-schutz.com	UK Dr. Schutz U.K Ltd. Unit 24, Anglo Business Park, Smeaton Close, Aylesbury Bucks HP19 8UP Contact: Richard Nelson Tel.: 0044 / 1296 437827 Fax: 0044 / 1296 334219 E-Mail: richard@dr-schutz.com	Ireland Dr. Schutz Ireland 35 Pic Du Jer Park, Ballinlough, Cork Contact: Paul O’Reardon Mobile: 0877678388 E-Mail: drschutzireland@gmail.com	North America Schutz NA 4701 Bath St 46, Philadelphia PA 19137, USA Contact: Sam Jamison Tel.: 001 / 877 272 4889 Mobile: 001 / 215 510 7874 E-Mail: sam@schutzNA.com
--	--	---	--

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.