



eukula[®]
WOOD.FLOOR.LOVE

eukula aqua hardwax oil

1. PRODUCT DESCRIPTION

Water-based hardwax oil, layer-forming. Suitable for lacquering wood and cork floors in residential buildings subject to normal wear. Recommended on common European wood species.

- Based on binding agents with a high proportion of renewable raw materials.
- Easy to use. Roller application, no polishing, no singledisc machine!
- Fast drying. Fully oiled parquet in 4 hours.
- Highlights the natural look of the wood. Naturally matte.
- Reduces the bonding of planks.
- Fire classification in accordance with EN 13501: Oak treated with the product and glued to screed from a thickness of 8 mm is flame retardant according to EN 14342 with the parameters specified therein in accordance with fire class C(fl)-s1.
- Low odor. With reduced emissions. Emissions tested building product according to AgBB guidelines. abZ: Z-157.10-272 .

Available variants: raw wood / ultra mat

Primer options:

Direct installation without special primer.

2. APPLICATION

Shake up well. Apply evenly and generously with a eukula roller at a minimum temperature of 15 °C Sand between coats with 120 grain sanding disc.

Please note:

- The professionally grouted and sanded sub-surface must be in a clean, dry condition, free of oil, wax and dust.
- Severely under-dried woods (e.g. sanded in renovation on under-floor heated wood) should be wet-mopped before applying lacquer, in order to avoid colour marks occurring during application.
- We always recommend the use of new dry paint rollers. Hardened coating residues can only be removed mechanically.



eukula[®]
WOOD.FLOOR.LOVE

eukula aqua hardwax oil

- The temperature of the floor and material must not fall below +15°C during application and drying time. Ideal conditions are in the range of 18–25 °C.
- The technical rules are to be observed.

3. CONSUMPTION

200 ml/m² in three coats of approx. 70 ml/m² each or in two coats of 100 ml/m² each.

4. DRYING TIME

Can be carefully walked on, or worked on again after the water has evaporated (1– 3 hours) . Can be used with caution 12 hours after the last layer has dried. Able to withstand moderate strain after 24 hours. The product is completely resistant after 7 days. The surface must not be wiped with a damp cloth during the first three days Refrain from placing rugs in the first 10–14 days. Carefully place the furniture.

General advice on drying and layer sequence

- Low temperatures, increased air humidity and poor ventilation can significantly extend the drying time.
- In order to avoid excessive swelling of the wood, we recommend only applying one coat by roller of water-based lacquer per day.
- In order to remove the water, accelerate drying and reduce moistening the wood we recommend using the Dr. Schutz drying fan TGI.
- An accelerated drying also reduces wood moistening and with it associated problems.

5. CLEANING & MAINTENANCE

After complete hardening use eukula care emulsion for cleaning and eukula H2Oil care to protect the floor. The eukula-care instructions apply to hardwax oil sealed/coated wood floors.

6. STORAGE

Protect from frost. Store in a cool dry place. Shelf life in unopened original containers from date of manufacture: 12 months. Note the imprinted date of manufacture.

Keep out of the reach of children.



eukula[®]
WOOD.FLOOR.LOVE

eukula aqua hardwax oil

If stored in changing temperatures and in opened canisters, dry particles can form. Filter these out with a sieve before using.

7. TECHNICAL DATA

Ingredients: water / modified vegetable oils / polyurethane / glycol ether / silicic acids / waxes / additives / preservation agents Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Decopaint 2004/42/IIA(i)(140)140 / GISCODE W2+ (1 component water-based sealer, VOC < 5%, NMP-free)

ADR/RID: Not a dangerous good as defined by transport regulations.

CLP/GHS: no labelling obligation.

Synthetic Micro Plastic Regulation: Do not dispose of residues or washing water in the drain. Clean work equipment mechanically after use (e.g., cloths); dispose of hardened residues as solid waste.

Further information on labelling and on safe handling can be found in the current Safety Data Sheet.

Even when using low-pollution products, the usual safety measures are to be observed. Keep away from children. Completely emptied containers can be disposed of with household waste or with the collection of recyclables.

8. SPECIAL NOTES

- Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of different batches, mix these in a separate container before using.
- All indications based on 23°C/50% rH/ 3-fold change of air per hour. Existing conditions can vary and account for different results. Reference wood: oak.

9. CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes.



eukula[®]
WOOD.FLOOR.LOVE

eukula aqua hardwax oil

- Safety Data Sheet available on request.
www.eukula.com / The quoted printed matter, as well as this Product Information in its updated form, is available on our homepage or on request from the address quoted below.

eukula – contact us

Germany
Headquarter (international)

Dr. Schutz GmbH
Holbeinstraße 17
53175 Bonn
Germany

phone +49 (228) 95352-40
fax +49 (228) 95352-46
email: export@dr-schutz.com
www.dr-schutz.com

United Kingdom

Dr. Schutz UK Ltd.
5-11 Mortimer Street
W1T 3HS London
United Kingdom

Contact: Sales Team
phone +44 (1296) 437827
email: sales@drschutz.co.uk

Ireland

Dr. Schutz Ireland
35 Pic Du Jer Park,
Ballinlough, Cork
T12 R9F9
Republic of Ireland

contact: Paul O'Reardon
mobile +353 87 767 8388
email: paul@drschutzireland.com

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability – which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.