



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula H 99 A

### 1. PRODUCT DESCRIPTION

Wood filler, alcohol-based. For mixing joint filler from sanding dust. For filling joints of wood/parquet floors. Can be used almost universally on all types of wood and cork floors. Can generally be used under all eukula surface treatments.

- Fast drying.
- Good filling capacity.
- No dark discoloration of joints under oil.
- Mild odour when working with the product.

### 2. APPLICATION

Shake up well. Mix with approx 5-10% (according to weight) of fine, metal-free wood dust from the sanded floor to fill. Fill the joints thoroughly with a stainless steel trowel. If necessary fill a second time after a short drying time. After drying sand the floor so that no remnants remain on the surface.

Please note:

- The professionally grouted and sanded sub-surface must be in a clean, dry condition, free of oil, wax and dust.
- Any dirt, waxes or old sealer residues located in the joints can lead to reduced adhesion and accelerated cracking of filler in the joints, sometimes even during final fine sanding.
- Fine sanding dust from disc-sanding machines is particularly recommended (single disc & multi disc machines, edge sanders). Dust from lateral sanding with a belt sander is not suitable.
- If necessary, it is better to chip out excessively wide joints.
- The temperature of the floor and material must not fall below +15°C during application and drying time. Ideal conditions are in the range of 18-25 °C.
- The technical rules are to be observed.
- Clean tools with acetone. Once cured, only mechanical removal is possible.

### 3. CONSUMPTION

40-50 ml/m<sup>2</sup> (20 m<sup>2</sup>/l)



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula H 99 A

Depending on the joints, sanding and absorbency of the wood, increased consumption is possible.

### 4. DRYING TIME

Can be further processed after approx. 60 minutes.

General advice on drying and layer sequence

- Low temperatures, increased air humidity and poor ventilation can significantly extend the drying time.
- Filling wider joints significantly increases the drying time.

### 5. STORAGE

Store in a cool dry place. Shelf life in unopened original containers from date of manufacture: 24 months. Note the imprinted date of manufacture.

Keep out of the reach of children.

### 6. TECHNICAL DATA

Ingredients: Alcohols / synthetic resin / polyester

Decopaint 2004/42/IIA(h)(750)750 / GISCODE G2 (Germany)

ADR/RID: UN 1263, 3/III

CLP/GHS: GHS02, GHS07, Danger Highly flammable liquid and vapour Causes serious eye irritation May cause drowsiness or dizziness Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor/... if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container according to local/regional/national/international regulation. UFI: 8PT0-H04R-300Y-MYAE

Further information on labelling and on safe handling can be found in the current Safety Data Sheet.



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula H 99 A

Even when using low-pollution products, the usual safety measures are to be observed. Keep away from children. Completely emptied containers can be disposed of with household waste or with the collection of recyclables.

### 7. SPECIAL NOTES

- Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of different batches, mix these in a separate container before using.
- All indications based on 23°C/50% rH/ 3-fold change of air per hour. Existing conditions can vary and account for different results. Reference wood: oak.

### 8. CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes.
- Safety Data Sheet available on request.

[www.eukula.com](http://www.eukula.com) / The quoted printed matter, as well as this Product Information in its updated form, is available on our homepage or on request from the address quoted below.



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

eukula H 99 A

## eukula – contact us

Germany  
Headquarter (international)

Dr. Schutz GmbH  
Holbeinstraße 17  
53175 Bonn  
Germany

phone +49 (228) 95352-40  
fax +49 (228) 95352-46  
email: [export@dr-schutz.com](mailto:export@dr-schutz.com)  
[www.dr-schutz.com](http://www.dr-schutz.com)

United Kingdom

Dr. Schutz UK Ltd.  
Unit 24, Anglo Business Park,  
Smeaton Close, Aylesbury Bucks  
HP19 8UP  
United Kingdom

contact: Richard Nelson  
phone +44 (1296) 437827  
fax +44 (1296) 334219  
email: [richard@drschutz.co.uk](mailto:richard@drschutz.co.uk)

Ireland

Dr. Schutz Ireland  
35 Pic Du Jer Park,  
Ballinlough, Cork  
T12 R9F9  
Republic of Ireland

contact: Paul O'Reardon  
mobile +353 87 767 8388  
email: [paul@drschutzireland.com](mailto:paul@drschutzireland.com)

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.