



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula exotic prime 201

### 1. PRODUCT DESCRIPTION

Waterbased primer. For application with a roller on sanded raw wood and cork floors. With warm accentuation of contrasts in the wood. Can be used almost universally on all types of wood and cork floors. Especially recommended for sealing of tropical wood species. Can be used under approved eukula sealers easy 30x, professional 31x, perform 46x.

- Based on special acrylate dispersions.
- pH acidic. Reduced activation of wood ingredients that tend to "bleed".
- Reduces the bonding of planks.
- Suitable for floors with subfloor heating.
- Solvent free, low emissions.

Emissions tested building product according to AgBB guidelines.

abZ No. Z-157. 10-157 under 1-component eukula finishes (Germany)

abZ No. Z-154. 10-155 under 2-component eukula finishes (Germany)

### 2. APPLICATION

Shake up well. Apply evenly and generously with a eukula roller at a minimum temperature of 15 °C After overnight drying, lacquer with approved eukula lacquers without sanding in between. For this purpose use a new roller.

Please note:

- The professionally grouted and sanded sub-surface must be in a clean, dry condition, free of oil, wax and dust.
- Subsequently applied lacquers can appear whitish on the surface during the wet phase, but become transparent when dry.
- Severely under-dried woods (e.g. sanded in renovation on under-floor heated wood) should be wet-mopped before applying lacquer, in order to avoid colour marks occurring during application.
- Clean tools with water. Hardened coating residues can only be removed mechanically. We always recommend the use of new dry paint rollers.
- The roller may only be used for further work with eukula exotic prime 201.
- The temperature of the floor and material must not fall below +15°C during application and drying time. Ideal conditions are in the range of 18-25 °C.
- The technical rules are to be observed.



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula exotic prime 201

### 3. CONSUMPTION

80–100 ml/m<sup>2</sup> (10–12 m<sup>2</sup>/l).

Apply thick layers for a good flow and uniform surface appearance and good protection. More product might be needed on rough or absorbent surfaces.

### 4. DRYING TIME

Can be walked on carefully, or worked on again, after about 6–12 hours. The product must be thoroughly dried.

General advice on drying and layer sequence

- Low temperatures, increased air humidity and poor ventilation can significantly extend the drying time.
- In order to avoid excessive swelling of the wood, we recommend only applying one coat by roller of water-based lacquer per day.
- In order to remove the water, accelerate drying and reduce moistening the wood we recommend using the Dr. Schutz drying fan TG1.
- An accelerated drying also reduces wood moistening and with it associated problems.

### 5. STORAGE

Protect from frost. Store in a cool dry place. Shelf life in unopened original containers from date of manufacture: 12 months. Note the imprinted date of manufacture.

Keep out of the reach of children.

If stored in changing temperatures and in opened canisters, dry particles can form. Filter these out with a sieve before using.

### 6. TECHNICAL DATA

Ingredients: water / polyacrylate / glycol ether / silicic acids / waxes / additives

Decopaint 2004/42/IIA(i)(140)140 / GISCODE W1 (1K-water-based sealer, VOC free) (Germany)

ADR/RID: Not a dangerous good as defined by transport regulations.

CLP/GHS: no labelling obligation. UFI: GJ10-9066-100X-R1K9

Further information on labelling and on safe handling can be found in the current Safety Data Sheet.



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula exotic prime 201

Even when using low-pollution products, the usual safety measures are to be observed. Keep away from children. Completely emptied containers can be disposed of with household waste or with the collection of recyclables.

### 7. SPECIAL NOTES

- Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of different batches, mix these in a separate container before using.
- All indications based on 23°C/50% rH/ 3-fold change of air per hour. Existing conditions can vary and account for different results. Reference wood: oak.
- The lacquer must not be mixed with other strato qualities.
- It is possible to apply the product on all types of wood. In the case of exotic woods it can lead to characteristic images specific to those wood types. We recommend pre-testing.

### 8. CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes.
- Safety Data Sheet available on request.

[www.eukula.com](http://www.eukula.com) / The quoted printed matter, as well as this Product Information in its updated form, is available on our homepage or on request from the address quoted below.



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula exotic prime 201

### eukula – contact us

Germany  
Headquarter (international)

Dr. Schutz GmbH  
Holbeinstraße 17  
53175 Bonn  
Germany

phone +49 (228) 95352-40  
fax +49 (228) 95352-46  
email: [export@dr-schutz.com](mailto:export@dr-schutz.com)  
[www.dr-schutz.com](http://www.dr-schutz.com)

United Kingdom

Dr. Schutz UK Ltd.  
Unit 24, Anglo Business Park,  
Smeaton Close, Aylesbury Bucks  
HP19 8UP  
United Kingdom

contact: Richard Nelson  
phone +44 (1296) 437827  
fax +44 (1296) 334219  
email: [richard@drschutz.co.uk](mailto:richard@drschutz.co.uk)

Ireland

Dr. Schutz Ireland  
35 Pic Du Jer Park,  
Ballinlough, Cork  
T12 R9F9  
Republic of Ireland

contact: Paul O'Reardon  
mobile +353 87 767 8388  
email: [paul@drschutzireland.com](mailto:paul@drschutzireland.com)

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula exotic prime 201

rules. On publication, this product information replaces and supersedes the validity of any previous versions.