



eukula[®]
WOOD.FLOOR.LOVE

eukula hardwax antislip R10 add

1. PRODUCT DESCRIPTION

Optional system component for addition to eukula hardwax oil+. Structure-imparting additive to increase slip resistance. Application in the final coat when applying the lacquer system.

- Liquid preparation for simplified application.
- Highly effective.
- Mixing ratio 10:1.
- Tested according to DIN EN 16165 A, slip class R10
- Emissions tested building product according to AgBB guidelines. abZ-Nr. Z-157.10-213 (Germany)

2. APPLICATION

Shake up well. Mix in to base system in a ratio of 1:10. Thinly roll out the finish coat evenly with approx. 50 ml/m².

Please note:

- Combined application with other components of the eukula hardwax system is optional.

3. CONSUMPTION

4-5 ml/m² at mixing ratio 10:1 in primer application. Range: 20 m² per 100 ml.

4. DRYING TIME

As given for the base system.

5. CLEANING & MAINTENANCE

As given for the base system.

In order to preserve the surface characteristics we recommend occasional subsequent lacquering care measure.

6. STORAGE

Store in a cool dry place. Shelf life in unopened original containers from date of manufacture: 24 months. Note the imprinted date of manufacture.



eukula[®]
WOOD.FLOOR.LOVE

eukula hardwax antislip R10 add

Keep out of the reach of children.

7. TECHNICAL DATA

Ingredients: aliphatic hydrocarbons (Repeated exposure may cause skin dryness or cracking.)
/ silicic acids / additives

ADR/RID: Not a dangerous good as defined by transport regulations.

CLP/GHS: no labelling obligation. UFI: PKE0-40TR-X006-CU5A

Further information on labelling and on safe handling can be found in the current Safety Data Sheet.

Even when using low-pollution products, the usual safety measures are to be observed. Keep away from children. Completely emptied containers can be disposed of with household waste or with the collection of recyclables.

8. CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes.
- Safety Data Sheet available on request.

www.eukula.com / The quoted printed matter, as well as this Product Information in its updated form, is available on our homepage or on request from the address quoted below.



eukula[®]
WOOD.FLOOR.LOVE

eukula hardwax antislip R10 add

eukula – contact us

Germany
Headquarter (international)

Dr. Schutz GmbH
Holbeinstraße 17
53175 Bonn
Germany

phone +49 (228) 95352-40
fax +49 (228) 95352-46
email: export@dr-schutz.com
www.dr-schutz.com

United Kingdom

Dr. Schutz UK Ltd.
Unit 24, Anglo Business Park,
Smeaton Close, Aylesbury Bucks
HP19 8UP
United Kingdom

contact: Richard Nelson
phone +44 (1296) 437827
fax +44 (1296) 334219
email: richard@drschutz.co.uk

Ireland

Dr. Schutz Ireland
35 Pic Du Jer Park,
Ballinlough, Cork
T12 R9F9
Republic of Ireland

contact: Paul O'Reardon
mobile +353 87 767 8388
email: paul@drschutzireland.com

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability – which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.