



eukula[®]
WOOD.FLOOR.LOVE

eukula oak antique conditioner

1. PRODUCT DESCRIPTION

Water-based salt solution ("lye"). Design pre-treatment for wood before impregnation with eukula oil. Leached wooden floors absorb oils particularly well. Particularly effective colour shades can be achieved with colour oils. Antique effect when treating oak.

Lyes react chemically with the natural wood ingredients. This results in a discolouration specific to the type of wood. The application is of course also possible on other types of wood than those mentioned here. The effect must be tested individually for the given wood. Lyes do not represent a protective surface treatment.

2. APPLICATION

Apply evenly to the professionally sanded floor using the T-Applicator with fur strip. After the water has dried, oil without further intermediate sanding.

Please note:

- The professionally grouted and sanded sub-surface must be in a clean, dry condition, free of oil, wax and dust.
- To achieve a perfect appearance an even application is essential.
- The temperature of the floor and material must not fall below +15°C during application and drying time. Ideal conditions are in the range of 18-25 °C.
- The technical rules are to be observed.

3. CONSUMPTION

80-100 ml/m² (10-12 m²/l).

Depending on the joints, sanding and absorbency of the wood, increased consumption is possible.

4. STORAGE

Protect from frost. Store in a cool dry place. Unlimited shelf life in unopened original container. Keep out of the reach of children.

5. TECHNICAL DATA



eukula[®]
WOOD.FLOOR.LOVE

eukula oak antique conditioner

Ingredients: water / acidic / Amines / Metal salts

ADR/RID: Not a dangerous good as defined by transport regulations.

CLP/GHS: no labelling obligation. UFI: 5YD0-K0YY-S00R-QF2V

Further information on labelling and on safe handling can be found in the current Safety Data Sheet.

Even when using low-pollution products, the usual safety measures are to be observed. Keep away from children. Completely emptied containers can be disposed of with household waste or with the collection of recyclables.

6. SPECIAL NOTES

- The drying times of oils on leached wood can deviate from the usual values. This should be taken into account especially for oil-water lacquer combination build-ups.
- Mixed installation of different types of wood may result in bleeding and transfer from one type of wood to another.
- Lyes work with the wood at hand. Uneven distribution of ingredients in different cuts, heartwood, sapwood can be visually enhanced. The effects of the wood used for the object may also differ from a wood sample. In case of doubt, we recommend a sample test in the object.
- Mixing different eukula conditioners is not recommended.

7. CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes.
- Safety Data Sheet available on request.

www.eukula.com / The quoted printed matter, as well as this Product Information in its updated form, is available on our homepage or on request from the address quoted below.



eukula[®]
WOOD.FLOOR.LOVE

eukula oak antique conditioner

eukula – contact us

Germany
Headquarter (international)

Dr. Schutz GmbH
Holbeinstraße 17
53175 Bonn
Germany

phone +49 (228) 95352-40
fax +49 (228) 95352-46
email: export@dr-schutz.com
www.dr-schutz.com

United Kingdom

Dr. Schutz UK Ltd.
Unit 24, Anglo Business Park,
Smeaton Close, Aylesbury Bucks
HP19 8UP
United Kingdom

contact: Richard Nelson
phone +44 (1296) 437827
fax +44 (1296) 334219
email: richard@drschutz.co.uk

Ireland

Dr. Schutz Ireland
35 Pic Du Jer Park,
Ballinlough, Cork
T12 R9F9
Republic of Ireland

contact: Paul O'Reardon
mobile +353 87 767 8388
email: paul@drschutzireland.com

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.