



eukula[®]
WOOD.FLOOR.LOVE

eukula refresher Classic

1. PRODUCT DESCRIPTION

Deeply effective care oil. Floor care for oxidative oiled floors. Deeply effective follow-up impregnation of tired, oiled wood floors as well as cork and OSB. Also suitable for industrially pre-oiled surfaces. Refreshes dull, especially stressed and intensively cleaned oil surfaces. For impregnated-oiled and hard-wax oiled surfaces. For wood floors of all load classes in residential and commercial areas.

- Based on vegetable oils, resins and carnauba wax.
- Good penetrating and high filling properties.
- Without film building, creates a natural, porous surface.
- Satin appearance.
- Mild odour when working with the product.
- Suitable for floors with subfloor heating.

Also suitable for impregnating furniture, wood panels, etc.

Not recommended for coated surfaces without grain enhancement, for example coatings with waterbased oils and other waterbased laquers.

Available variants: Colorless / White (only recommended for surfaces that have been previously treated with a white oil)

2. APPLICATION

Clean the floor thoroughly before care treatment with a slightly damp mop and allow the floor to dry. Shake up well. Apply a thin layer of the product with a cloth, brush or roller. Saturate more absorbent wood. Avoid excess application! After allowing to soak in for 15-30 minutes polish the remaining excess with a monodisc machine and a white pad. Do not allow any moist oil to remain on the surface. The oil must never dry on the floor during the process.

Please note:

- Apply required amounts of oil and remove excess material from the surface.
- In the case of severe damage to the surface and high absorbency, another application may be necessary after the oil has dried.
- Carefully remove stains and light scratches with fine sandpaper before maintenance.
- The application with the T-Wiper and cloth-strip is also recommended.



eukula[®]
WOOD.FLOOR.LOVE

eukula refresher Classic

- For polishing large areas we recommend using a monodisc-machine. Larger surplus can be absorbed with a cloth placed underneath. Alternatively, you can work with cloths by hand on small areas.
- Remove any surplus oil from the joints after 1 day with a green pad.
- The temperature of the floor and material must not fall below +15°C during application and drying time. Ideal conditions are in the range of 18-25 °C.
- Switch off under-floor heating well in advance.

3. CONSUMPTION

10-20 ml/m² (50-100 m²/l).

More product might be needed on rough or absorbent surfaces.

4. DRYING TIME

Can be walked on carefully, or worked on again, after about 6-12 hours. The surface must not be wiped with a damp cloth during the first three days. Refrain from placing rugs in the first 10-14 days. Carefully place the furniture.

Please note:

- Low temperatures, increased air humidity and poor ventilation can significantly extend the drying time.
- In the case of soft and tropical woods, wood ingredients can lead to delays in drying, or result in an impaired appearance.
- Oil hardening can be accelerated via air movement. We recommend our Dr. Schutz TGI drying fan.

5. STORAGE

Store in a cool dry place. Shelf life in unopened original containers from date of manufacture: 24 months. Note the imprinted date of manufacture.

Keep out of the reach of children.

Remove any skin which may have formed before use.

6. TECHNICAL DATA

Ingredients: natural vegetable oils (such as linseed oil, safflower oil, hemp oil) / modified vegetable oils / Carnauba wax / aliphatic hydrocarbons / glycol ether / drying agents free of lead and cobalt



eukula[®]
WOOD.FLOOR.LOVE

eukula refresher Classic

Decopaint 2004/42/IIA(f)(700)700 / GISCODE Ö60 + (strongly solvent-based oils / waxes, dearomatised, oxime-free)

ADR/RID: Not a dangerous good as defined by transport regulations.

CLP/GHS: no labelling obligation. UFI: NX80-T0JA-D00G-MDPU / Y4GJ-N4YT-300M-X7E4 White

Further information on labelling and on safe handling can be found in the current Safety Data Sheet.

Even when using low-pollution products, the usual safety measures are to be observed. Keep away from children. Completely emptied containers can be disposed of with household waste or with the collection of recyclables.

7. SPECIAL NOTES

- Warning! Danger of self-combustion of oil-soaked working materials, such as cloths, fleeces, sanding dust, etc. These should be enclosed in an air-tight metal container, or soaked with water and disposed of in a fire-safe way. The oil itself is not self-combusting.
- All indications based on 23°C/50% rH/ 3-fold change of air per hour. Existing conditions can vary and account for different results. Reference wood: oak.
- Oiled surfaces smell. The smell diminishes with increasing drying in the course of days. Ensure good ventilation after installation.
- Oiled surfaces show a characteristic yellowing tendency. This can lead to conspicuous areas, especially in the case of bright floors and light coverage.

8. CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes.
 - Safety Data Sheet available on request.
 - Please observe eukula care instructions for for wood and cork floors.
- www.eukula.com / The quoted printed matter, as well as this Product Information in its updated form, is available on our homepage or on request from the address quoted below.



eukula[®]
WOOD.FLOOR.LOVE

eukula refresher Classic

eukula – contact us

Germany
Headquarter (international)

Dr. Schutz GmbH
Holbeinstraße 17
53175 Bonn
Germany

phone +49 (228) 95352-40
fax +49 (228) 95352-46
email: export@dr-schutz.com
www.dr-schutz.com

United Kingdom

Dr. Schutz UK Ltd.
Unit 24, Anglo Business Park,
Smeaton Close, Aylesbury Bucks
HP19 8UP
United Kingdom

contact: Richard Nelson
phone +44 (1296) 437827
fax +44 (1296) 334219
email: richard@drschutz.co.uk

Ireland

Dr. Schutz Ireland
35 Pic Du Jer Park,
Ballinlough, Cork
T12 R9F9
Republic of Ireland

contact: Paul O'Reardon
mobile +353 87 767 8388
email: paul@drschutzireland.com

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical



eukula[®]
WOOD.FLOOR.LOVE

eukula refresher Classic

rules. On publication, this product information replaces and supersedes the validity of any previous versions.