



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula trowel prime 220

### 1. PRODUCT DESCRIPTION

Waterbased primer. Optimized for trowel application to wood/parquet floors. To be used for priming raw wood in trowel application as well as for intermediate trowel filling between coats. For wood floors with closed joints. Can be used under all eukula finishes.

- Effectively increases the volume of subsequent applied finishes.
- Fast drying. Reduced wood raising.
- Reduces the bonding of planks.
- Due to the especially fast drying of trowel applied layers, this is particularly recommended for quick lacquering, 2-3 times troweling, one generous finish coat with roller.

Emissions tested building product according to AgBB guidelines.

abZ No. Z-157. 10-157 under 1-component eukula finishes (Germany)

abZ No. Z-154. 10-155 under 2-component eukula finishes (Germany)

### 2. APPLICATION

Shake up well. Apply with a stainless steel trowel to create a smooth surface. After a short drying time, apply crosswise to the floor a second time. After drying, apply lacquer without sanding in between.

Please note:

- The professionally grouted and sanded sub-surface must be in a clean, dry condition, free of oil, wax and dust.
- For intermediate trowel filling between coats the entire lacquered areas must be sanded.
- Clean tools with water. Hardened coating residues can only be removed mechanically. We always recommend the use of new dry paint rollers.
- The temperature of the floor and material must not fall below +15°C during application and drying time. Ideal conditions are in the range of 18-25 °C.
- The technical rules are to be observed.

### 3. CONSUMPTION

On raw wood: 40-50 ml/m<sup>2</sup> (20 m<sup>2</sup>/l) More product might be needed on rough or absorbent surfaces.

For intermediate troweling between coats: 10-20 ml/m<sup>2</sup> (50-100 m<sup>2</sup>/l).



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula trowel prime 220

### 4. DRYING TIME

Can be carefully walked on, or worked on again after the water has evaporated (30–60 minutes)

### 5. STORAGE

Protect from frost. Store in a cool dry place. Shelf life in unopened original containers from date of manufacture: 12 months. Note the imprinted date of manufacture.

Keep out of the reach of children.

If stored in changing temperatures and in opened canisters, dry particles can form. Filter these out with a sieve before using.

### 6. TECHNICAL DATA

Ingredients: water / polyacrylate / glycol ether / silicic acids / waxes / additives / Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Decopaint 2004/42/IIA(i)(140)140 / GISCODE W2+ (1 component water-based sealer, VOC < 5%, NMP-free)

ADR/RID: Not a dangerous good as defined by transport regulations.

CLP/GHS: no labelling obligation. UFI: N1D0-10DM-E009-FPP5

Further information on labelling and on safe handling can be found in the current Safety Data Sheet.

Even when using low-pollution products, the usual safety measures are to be observed. Keep away from children. Completely emptied containers can be disposed of with household waste or with the collection of recyclables.

### 7. SPECIAL NOTES

- Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of different batches, mix these in a separate container before using.
- All indications based on 23°C/50% rH/ 3-fold change of air per hour. Existing conditions can vary and account for different results. Reference wood: oak.
- Trowel priming generally not used in areas subject to heavy wear, nor in very absorbent or underdried wood types. In such cases we recommend priming with a roller application.

### 8. CROSS-REFERENCE



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula trowel prime 220

Our following publications in their updated form are valid as an integral part of this fact sheet:

General notes on the application of eukula finishes.

Safety Data Sheet available on request.

[www.eukula.com](http://www.eukula.com) / The quoted printed matter, as well as this Product Information in its updated form, is available on our homepage or on request from the address quoted below.



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula trowel prime 220

### eukula – contact us

Germany  
Headquarter (international)

Dr. Schutz GmbH  
Holbeinstraße 17  
53175 Bonn  
Germany

phone +49 (228) 95352-40  
fax +49 (228) 95352-46  
email: [export@dr-schutz.com](mailto:export@dr-schutz.com)  
[www.dr-schutz.com](http://www.dr-schutz.com)

United Kingdom

Dr. Schutz UK Ltd.  
Unit 24, Anglo Business Park,  
Smeaton Close, Aylesbury Bucks  
HP19 8UP  
United Kingdom

contact: Richard Nelson  
phone +44 (1296) 437827  
fax +44 (1296) 334219  
email: [richard@drschutz.co.uk](mailto:richard@drschutz.co.uk)

Ireland

Dr. Schutz Ireland  
35 Pic Du Jer Park,  
Ballinlough, Cork  
T12 R9F9  
Republic of Ireland

contact: Paul O'Reardon  
mobile +353 87 767 8388  
email: [paul@drschutzireland.com](mailto:paul@drschutzireland.com)

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical



**eukula**<sup>®</sup>  
WOOD.FLOOR.LOVE

## eukula trowel prime 220

rules. On publication, this product information replaces and supersedes the validity of any previous versions.