



## Carpetlife Granulate

### 1 PRODUCT DESCRIPTION

A carpet cleaning powder with excellent dirt releasing properties for the thorough and quick professional cleaning of partial sections and full textile floors. Ideally suitable for the cleaning of moisture-sensitive flooring types, constructions and installation types (e. g. lose laid, velcro fastened and tightened carpeting, when using water-soluble glue, for false flooring constructions). No shrinking or formation of waves. The flooring is not wetted and can be walked on during the cleaning procedure. Prevents development of a grey surface film after cleaning and acceleration in the resoiling of the floor. Maintains the depth and freshness of colour of the floor covering. Minimised development of dust due to an optimised dispersion of granule sizes. For the application in the living area as well as the professional cleaning of the industrial object.

### 2 AREAS OF APPLICATION

Suitable for velour flooring made of all kinds of synthetic fibres up to a pile depth of 10 mm as well as short loop pile carpeting. Not suitable for coarse loop pile carpeting, shag and natural fibre flooring made of coconut, jute, eelgrass, rice straw, paper, cotton. The application on needle punched non-woven flooring, berber, pure new wool and sisal flooring is possible depending on the flooring and the object and should be checked in advance on a suitable area or discussed with our Technical Application Advisory Service.

Please pay attention to our technical instructions specifically for floors and buildings under [www.dr-schutz.com](http://www.dr-schutz.com)

### 3 METHOD OF APPLICATION

Clean the carpeting thoroughly with a high- performance brush extraction appliance ( e.g. the Tebo Brush Vacuum Cleaner). Spray - but do not soak - stains and strongly soiled sections of the flooring evenly with a mist of Fresh-Up 2 in 1. Thoroughly mix Carpetlife with Tebo-active granules and spread evenly onto the stained areas.

Carpetlife Granulat gut durchmischen und gleichmäßig auf die verschmutzten Bereiche aufstreuen. Apply the granules thoroughly with a suitable brush massaging appliance (e.g. Carpetlife Profi 350) using counter-rotating brushes suitable for the flooring, working lengthways and crossways. Die Auswahl der Bürsten an der Empfindlichkeit des Polmaterials und der Intensität der Verschmutzung orientieren. Should there be evidence of grooves forming in the carpet pile at the beginning of the cleaning operation, use softer brushes.. Work in sections during cleaning, meaning that the cleaning granules should be spread and applied in partial sections.

After allowing it to dry completely (approx. 1 hour), take up the granules with the dirt contained within with the Carpetlife Profi 350 on the entire floor area or vacuum clean with a brush vacuum cleaner. Ensure that the collection container is emptied resp. the dust bag is changed with sufficient frequency. In highly soiled areas, treat the floor several times if necessary. Remove stubborn stains with a suitable stain removal product.

Special procedures are to be observed when cleaning the following textile floor coverings:

- Needle punched non-woven flooring, sisal flooring
  - do not use pre-treatment spray (Fresh-Up 2 in 1)
  - apply Carpetlife Tebo-active granules very sparingly to any dirt remaining after vacuum



## Carpetlife Granulate

- cleaning has been performed and work them in.
  - Berber, high-pile floor coverings, soft velours
    - only work in the direction of the loops or fibres respectively (not lengthways and crossways).

**Notes:** Before commencing, test the floor for colourfastness and material suitability as well as the suitability for the treatment with a brush appliance in an inconspicuous place.

### 4 CONSUMPTION

50-75 g per m<sup>2</sup>, depending on soiling

### 5 STORAGE

Store in cool, dry conditions in well sealed receptacles. Store under lock and key and out of the reach of children.

### 6 TECHNICAL DATA

Ingredients: contains under 5% anionic tensides, under 5% non ionic tensides. Contains METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE, OCTYLISOTHIAZOLINONE, perfums, solvents, cellulose.

pH value: about 7 (10 % in water).

ADR/RID: no dangerous good according ADR

CLP: The product is not classified according to the CLP regulation.

EUH208 Contains 2-octyl-2H-isothiazol-3-one, 5-chloro-2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Completely emptied canisters can be disposed of in domestic waste, or taken to a recycling centre.

### 7 SPECIAL NOTES

Please pay attention to our technical instructions specifically for floors and buildings under [www.dr-schutz.com](http://www.dr-schutz.com)

### 8 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of Dr. Schutz finishes
- Safety data sheet available on request.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage [www.dr-schutz.com](http://www.dr-schutz.com) or on request from the address quoted below.

## Carpetlife Granulate



### Dr. Schutz – We Care About Floors

Headquarter  
Dr. Schutz GmbH  
Holbeinstraße 17  
D-53175 Bonn  
Tel.: +49 (0)228 / 95 35 2-40  
Fax: +49 (0)228 / 95 35 2-46  
E-Mail: [export@dr-schutz.com](mailto:export@dr-schutz.com)  
[www.dr-schutz.com](http://www.dr-schutz.com)

UK  
Dr. Schutz U.K Ltd.  
Unit 24, Anglo Business Park,  
Smeaton Close, Aylesbury Bucks  
HP19 8UP

Contact: Richard Nelson  
Tel.: +44 (0)1296 437827  
Fax: +44 (0)1296 334219  
E-Mail: [richard@dr-schutz.com](mailto:richard@dr-schutz.com)

Ireland  
Dr. Schutz Ireland  
35 Pic Du Jer Park,  
Ballinlough, Cork

Contact: Paul O'Reardon  
Mobile: 0877678388  
E-Mail: [drschutzireland@gmail.com](mailto:drschutzireland@gmail.com)

North America  
Schutz NA  
4701 Bath St 46  
Philadelphia, PA 19137  
USA

Contact: Sam Jamison  
Tel.: +1(877) 272- 4889  
Mobile: +1(215) 510- 7874  
E-Mail: [sam@schutzNA.com](mailto:sam@schutzNA.com)

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.