

## Click Sealer



### 1 PRODUCT DESCRIPTION

A high-quality impregnation agent to protect the edges of laminate and sealed wood and cork floors. Reduces the risk of surface swelling caused by dampness at the edges.

### 2 AREAS OF APPLICATION

EN 13329-defined laminate floor coverings and sealed wood floors. For floorings with a surface of paper-décor the application may be reduced due to a possible colour change. Therefore, it is recommended to previously test on a sample.

Please pay attention to our technical instructions specifically for floors and buildings under [www.dr-schutz.com](http://www.dr-schutz.com).

### 3 APPLICATION

Shake Click Sealer well before use. Then spread it thinly onto the dry floor and work it into the seams using a spatula made of plastic or high-grade steel-flex. Thoroughly remove the excessive impregnation material with the spatula. Then polish the surface with a soft non-fraying cloth or the SRP1 monodisc with a white pad until a uniform sheen is achieved. To avoid Click Sealer from drying too soon, always treat only small sections. After finishing leave to dry polished surface overnight before you walk on the floor again. Footsteps that may occur after drying can be equalised by polishing with a smooth brush.

**Note: Warning!** While drying, due to contact with oxygen in the air, the used cloths or pads could self-ignite in case of heat deceleration. Therefore leave used cloths or pads spread out or keep them in water or locked up in containers. Ensure sufficient air during and after application of product. Do not inhale product fumes. If Click Sealer has been swallowed, do not induce vomiting. Immediately seek a doctor and show label or product information.

### 4 CONSUMPTION

250 ml = 40 m<sup>2</sup>

### 5 STORAGE

Click Sealer should be stored in a cool, dry place in its closed original container. Protect from frost. Keep locked up and out of the reach of children.

## Click Sealer



### 6 TECHNICAL DATA

Data on ingredients (EC recommendation): natural oils and waxes, aliphatic hydrocarbons, unleaded dry substances.

pH level: cannot be determined, product is solvent based.

Product code for cleaning and care products (Giscode): GH 10.

ADR/RID: not a dangerous good as defined by transport regulations.

CLP: The product is not classified according to the CLP regulation.

EUH066 Repeated exposure may cause skin dryness or cracking.

Completely emptied canisters can be disposed of in domestic waste, or taken to a recycling centre.

### 7 SPECIAL NOTES

Please pay attention to our technical instructions specifically for floors and buildings under [www.dr-schutz.com](http://www.dr-schutz.com).

### 8 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of Dr. Schutz finishes
- Safety data sheet available on request.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage [www.dr-schutz.com](http://www.dr-schutz.com) or on request from the address quoted below.

#### Dr. Schutz – We Care About Floors

Headquarter  
Dr. Schutz GmbH  
Holbeinstraße 17  
D-53175 Bonn  
Tel.: +49 (0)228 / 95 35 2-40  
Fax: +49 (0)228 / 95 35 2-46  
E-Mail: [export@dr-schutz.com](mailto:export@dr-schutz.com)  
[www.dr-schutz.com](http://www.dr-schutz.com)

UK  
Dr. Schutz U.K Ltd.  
Unit 24, Anglo Business Park,  
Smeaton Close, Aylesbury Bucks  
HP19 8UP

Contact: Richard Nelson  
Tel.: +44 (0)1296 437827  
Fax: +44 (0)1296 334219  
E-Mail: [richard@dr-schutz.com](mailto:richard@dr-schutz.com)

Ireland  
Dr. Schutz Ireland  
35 Pic Du Jer Park,  
Ballinlough, Cork

Contact: Paul O'Reardon  
Mobile: 0877678388  
E-Mail: [drschutzireland@gmail.com](mailto:drschutzireland@gmail.com)

North America  
Schutz NA  
4701 Bath St 46  
Philadelphia, PA 19137  
USA

Contact: Sam Jamison  
Tel.: +1(877) 272- 4889  
Mobile: +1(215) 510- 7874  
E-Mail: [sam@schutzNA.com](mailto:sam@schutzNA.com)

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.