Version: 20.09.2017

### **Premium Hardwax Care**

### 1 PRODUCT DESCRIPTION

Water-based care product on a wax basis for the regular visual refreshing of hard-wax oiled wood and cork floors.

- Protects the floor against abrasion and the wood against water.
- Ready to use.
- Wipe-proof, can be mopped after drying.
- Matt.

### 2 SUITABLE FOR

For refreshing oxidative oiled wood and parquet floors, as well as oiled cork floors and oiled OSB, especially surfaces oiled with **Dr. Schutz Premium Hardwax Oil +**. Also suitable for industrially pre-oiled surfaces with high grain enhancement. In the case of UV-oiled surfaces we recommend testing beforehand. Not suitable for waterbased sealed surfaces without grain enhancement.

### 3 APPLICATION

Clean the floor well and allow to dry. Shake up **Dr. Schutz Hardwax Care** thoroughly. Apply thinly and evenly in undiluted application as complete care with a soft, fluff-free cloth, or with the polish applicator, free of streaks in the direction of the wood grain. The product is self-hardening and needs no polishing.

#### Please note:

- During application avoid strong sunlight and draughts, turn off floor heating beforehand.
- Temperature of floor and material must not fall below +15°C during application and drying time.
- It is also possible to apply the product in the framework of maintenance cleaning, diluted in a ration of 1:100 in water, using a mop.
- The build-up of too many layers of care product is to be avoided. By strip-cleaning with euku intensiv layers of care product can be removed.
- Polishing with a high-speed machine after drying is possible.
- Clean tools and implements with water.

The protection of the floor remains preserved if **Dr. Schutz Hardwax Care** is regularly applied after strip-cleaning. The care cycle is dependent on the degree of wear and tear:

- Slightly used floors (e.g. in living and bedrooms, office rooms without public access) about once or twice a year, as required.
- Medium used floors (e.g. in corridors, on staircases, in office rooms with public access) about every 3 to 6 months, frequently used areas also more often.
- Especially heavily frequented floors (e.g. in pubs, restaurants, shops, department stores, schools, or in the case of dance-floors) every 4 to 8 weeks, or more often.

# 4 COVERAGE

Version: 20.09.2017

### **Premium Hardwax Care**

50 m<sup>2</sup> (20 ml/m<sup>2</sup>)

### 5 CURING

When using the product undiluted as complete care, allow the area to dry out well before use (12 hours, ideally overnight, at 23 °C, 50% rel. air humidity, ventilation).

Low temperatures, high humidity and poor ventilation can prolong the drying time substantially.

### 6 MAINTENANCE

### 7 STORAGE

Store in a cool, dry place in the closed original canister. Keeps for at least 24 months in unopened original canister from the date of manufacture. Keep locked up and out of the reach of children.

## 8 TECHNICAL DATA

Contains substances: water, polyacrylat, glycolether, silicic acids, waxes, additives. Contains a mixture of: 5-chlorine-2-methyl-2H-isothiazol-3-on and 2-methyl-2H-isothiazol-3-on. May produce an allergic reaction.

voc (g/l) 49 (ISO11890) / GISCODE: GE10

ADR/RID: not a dangerous good.

CLP: no obligation to be labelled as hazardous.

Even when using low-pollution products, the usual safety measures are to be observed. Keep out of the reach of children. Completely emptied canisters can be disposed of in domestic waste, or taken to the recycling centre.

## 9 SPECIAL NOTES

- When applying to UV-sealed pre-finished wood floors, we recommend testing beforehand for adhesion and wetting. The pre-finished wooden floor must have a factory-applied edge-impregnation, or have its joints impregnated after being laid to prevent water penetration.
- Not suitable to impregnated-oiled surfaces. For these we recommend euku refresher.
- euku wax easily forms layers. In the case of excessive layers of care product it is possible to strip-clean the floor with Intensive Cleaner for Parquet&Corc.

## 10 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

Version: 20.09.2017

### **Premium Hardwax Care**

- General notes on the application of Dr. Schutz finishes
- Safety data sheet available on request.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage www.dr-schutz.com or on request from the address quoted below.

#### Dr. Schutz - We Care About Floors

Headquarter Dr. Schutz GmbH Holheinstraße 17 D-53175 Bonn Tel.: +49 (0)228 / 95 35 2-40

Fax: +49 (0)228 / 95 35 2-46 E-Mail: export@dr-schutz.com www.dr-schutz.com

Dr. Schutz U.K Ltd. Unit 24, Anglo Business Park, Smeaton Close, Aylesbury Bucks HP19 8UP

Contact: Richard Nelson Tel.: +44 (0)1296 437827

Fax: +44 (0)1296 334219 E-Mail: richard@dr-schutz.com Ireland Dr. Schutz Ireland 35 Pic Du Jer Park. Ballinlough, Cork

Contact: Paul O'Reardon Mobile: 0877678388 E-Mail: land@gmail.com

North America Schutz NA 4701 Bath St 46 Philadelphia PA 19137

USA

Contact: Sam Jamison Tel.: +1 (877) 272-4889 drschutzire- Mobile: +1 (215) 510-7874 E-Mail: sam@schutzNA.com

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.