



strato intensive prime 201 (2019)

1 PRODUCT DESCRIPTION

Waterbased lacquer primer with warm accentuation of the woods color.

- Roller primer for wood and cork floors
- Especially recommended for priming on exotic wood species.
- Reduces side-bonding.
- Suitable under approved strato-finishes easy 30x, professional 31x, perform 46x.
- Suitable for all types of wood
- Based on special high-quality acrylate dispersions
- Quick drying.
- Suitable for under-floor heated floors.
- Reduced roughening of the wood.
- Can be used under all strato-sealers.
- Giscode W2+
- Fire classification in accordance with EN 13501: oak, (8mm thick) glued onto a screed floor and treated with the product according to the parameters set in EN 14342, has low flammability corresponding to the fire classification C(fl)-s1

2 AREAS OF APPLICATION

For priming wood and parquet floors before finish with strato lacquers.

3 APPLICATION

Shake up **strato intensive prime 201** well! Apply evenly and generously with the strato-Roller.

Please note:

- The subsurface must be professionally sanded and grouted before application and must be clean and dry, free of oil, wax and dust.
- In order to remove the water, accelerate drying and reduce moisture in the wood, we recommend using the **Dr. Schutz Drying Fan TG1**.
- Wood which has largely been dried from below (e.g. in renovation sanding on an under-heated floor) should be wet-mopped before lacquering, in order to avoid colour marks in the process.
- Room and material temperature must not fall below +15°C during application and drying time.

4 CONSUMPTION

approx. 80-100 ml/m² per coat (10-12 m²/l).

For best results and an even surface image, work in thick layers. In the case of highly absorbing wood increased consumption is possible.

5 DRYING TIME

Can be walked on carefully and worked on again after evaporation of water, approx. 1-3 hours (at 20 °C, 50% relative humidity and air movement).



strato intensive prime 201 (2019)

In order to avoid excess soaking of the wood, only one rolled coat of water-based lacquer is recommended per day. Low temperatures, increased humidity and poor ventilation can prolong drying time substantially.

7 STORAGE

Protect from frost. Store in a cool dry place. Can be stored for 12 months from date of manufacture in unopened original canister. Keep coating materials out of the reach of children.

If stored in changing temperatures and in opened canisters, dry parts can form. Filter these out with a sieve before using.

8 TECHNICAL DATA

Contains substances: water, polyacrylates, silicic acid, glycol ethers, additives.

voc (g/l) 45 (ISO11890) / Decopaint 2004/42/IIA(i)(140)140.

GISCODE: W2+ / MALCode 0-1

ADR/RID: not a dangerous good as defined by transport regulations.

CLP: The product is not classified according to the CLP regulation.

Even when using low pollution products, the usual safety measures are to be observed. Keep out of the reach of children. Completely emptied canisters can be disposed of in domestic waste.

9 SPECIAL NOTES

- Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of a different batch, mix this in a separate container before using.
- The used roller can't further be used with other strato qualities.
- strato intensive prime 201 can't be mixed with other strato qualities.
- Clean working tools with water. We recommend that you leave the well-washed roller fully covered in water, in order to avoid it drying out. However, when the roller is used anew for application, no water must be allowed to mix with the lacquer.
- It is possible to apply the product to all types of wood. In the case of exotic woods, their characteristic appearance may be affected by the specific properties of the wood. We recommend testing beforehand.

10 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes
- Safety data sheet available on request.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage www.eukula.com or on request from the address quoted below.



strato intensive prime 201 (2019)

eukula – We Care About Wood Floors

Headquarter

Dr. Schutz GmbH
Holbeinstraße 17
D-53175 Bonn
Tel.: + 49 228 / 95 35 2-40
Fax: + 49 228 / 95 35 2-46
E-Mail: export@dr-schutz.com
www.dr-schutz.com

UK

Dr. Schutz U.K Ltd.
Unit 24, Anglo Business Park,
Smeaton Close, Aylesbury Bucks
HP19 8UP

Contact: Richard Nelson
Tel.: 0044 / 1296 437827
Fax: 0044 / 1296 334219
E-Mail: richard@dr-schutz.com

Ireland

Dr. Schutz Ireland
35 Pic Du Jer Park,
Ballinlough, Cork

Contact: Paul O'Reardon
Mobile: 0877678388
E-Mail: drschatzireland@gmail.com

North America

Schutz NA
4701 Bath St 46, Philadelphia PA
19137, USA

Contact: Sam Jamison
Tel.: 001 / 877 272 4889
Mobile: 001 / 215 510 7874
E-Mail: sam@schutzNA.com

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.