# Dr. Schutz

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 5 Revision: 03.02.2017

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Basis)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

SU21 Consumer uses: Private households / general public / consumers

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Knife filler/ Surfacer
- · 1.3 Details of the supplier of the safety data sheet
- Company/undertaking identification:

Dr. Schutz GmbH Holbeinstr. 17 D-53175 Bonn Germany

Tel.: +49(0)228-95352-0, Fax: +49(0)228-95352-28 info@dr-schutz.com

For the UK and Ireland:

Dr. Schutz U.K.

Unit 24

Anglo Buisness Park,

Smeaton Close Aylesbury

Bucks HP19 8UP

Tel.: 0044/1296-437827 Fax: 0044/1296-334219 E-Mail: steve@dr-schutz.com

· Further information obtainable from:

Department for product development

E-Mail: steve@dr-schutz.com

· 1.4 Emergency telephone number:

Dr. Schutz U.K. steve@dr-schutz.com

0044 (0) 1296 437827(mon - fri 9am-5pm)

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)



# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 5 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Basis)

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

styrene

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

### · Dangerous components:

CAS: 100-42-5

styrene

10-25%

EINECS: 202-851-5 Index number: 601-026-00-0

Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319

Additional information:

For the wording of the listed hazard phrases refer to section 16.

The content of benzene (EINECS-N° 200-753-7) in components is below 0,1 % (Annotation P annex I of directive 67/548/EC).

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

# Dr. Schutz®

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 5 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Basis)

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Rinse out mouth and then drink plenty of water.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full iet

Not applicable.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

(Contd. on page 4)



# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 5 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Basis)

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Exposure limit values:

### 100-42-5 styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

- **DNELs** No further relevant information available.
- PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Occupational exposure controls:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

· Protection of hands:

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Natural rubber, NR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Light weight protective clothing

# Dr. Schutz®

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 5 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Basis)

(Contd. of page 4)

SECTION 9: Physical and chemical pro	perties		
· 9.1 Information on basic physical and o	9.1 Information on basic physical and chemical properties		
· General Information	• •		
· Appearance:			
Form: Colour:	Pasty Black		
· Odour:	Characteristic		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/freezing point: Initial boiling point and boiling range	Undetermined.		
· Flash point:	37°C (Seta Flash Closed Cup)		
· Flammability (solid, gas):	Not applicable.		
Ignition temperature:	480°C		
· Decomposition temperature:	Not determined.		
· Auto-ignition temperature:	Product is not selfigniting.		
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.		
· Explosion limits:			
Lower:	1.2Vol %		
Upper:	8.9Vol %		
· Vapour pressure at 20°C:	6hPa		
· Density at 20°C:	2.23g/cm <sup>3</sup>		
Relative density	Not determined.		
· Vapour density	Not determined.		
· Evaporation rate	Not determined.		
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.		
· Partition coefficient: n-octanol/water:	Not determined.		
	NOT GETERMINEG.		
· Viscosity: Dynamic:	Not determined.		
Kinematic:	Not determined.		
· Solvent content:			
Organic solvents:	19.9%		
VOC (EC)	13,59%		
· 9.2 Other information	No further relevant information available.		

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity see section "Possibility of hazardous reactions".
- · 10.2 Chemical stability No information available.
- Conditions to avoid: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

# Dr. Schutz®

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 5 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Basis)

(Contd. of page 5)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
100-42-5	styrene		
Oral	LD50	5,000 mg/kg (rat)	
Inhalative	LC50/4h	24 mg/l (rat)	

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	
15 01 04	metallic packaging	

(Contd. on page 7)



# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 5 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Basis)

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN3269
· 14.2 UN proper shipping name · ADR · IMDG, IATA	3269 POLYESTER RESIN KIT solution POLYESTER RESIN KIT solution
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
<ul> <li>· 14.6 Special precautions for user</li> <li>· EMS Number:</li> <li>· Stowage Category</li> </ul>	Warning: Flammable liquids. F-E,S-D A
· 14.7 Transport in bulk according to Annex II of  Marpol and the IBC Code Not applicable.	
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: SEE 3 E
<ul><li>· IMDG</li><li>· Limited quantities (LQ)</li><li>· Excepted quantities (EQ)</li></ul>	5L Code: See SP340
· UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT SOLUTION, 3, III

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 5 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Basis)

(Contd. of page 7)

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

## · Department issuing SDS: Department for product development

### · Contact:

Dr. Reindl

Dr. Reindl

### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

## · \* Data compared to the previous version altered.