## Dr. Schutz

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 7 Revision: 03.02.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Hardener)
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU21 Consumer uses: Private households / general public / consumers
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC10 Roller application or brushing
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Company/undertaking identification:

Dr. Schutz GmbH Holbeinstr. 17 D-53175 Bonn Germany

Tel.: +49(0)228-95352-0, Fax: +49(0)228-95352-28 info@dr-schutz.com

For the UK and Ireland:

Dr. Schutz U.K.

Unit 24

Anglo Buisness Park,

Smeaton Close Aylesbury

Bucks HP19 8UP

Tel.: 0044/1296-437827 Fax: 0044/1296-334219 E-Mail: steve@dr-schutz.com

- · Further information obtainable from: Department for product development
- · 1.4 Emergency telephone number:

Dr. Schutz U.K. steve@dr-schutz.com

0044 (0) 1296 437827(mon - fri 9am-5pm)

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Self-react. E H242 Heating may cause a fire.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)



# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 7 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Hardener)

· Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

dibenzoyl peroxide

· Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 94-36-0	dibenzoyl peroxide	25-50%		
EINECS: 202-327-6 Index number: 617-008-00-0	<ul> <li>Org. Perox. B, H241;</li> <li>Aquatic Acute 1, H400;</li> <li>Eye Irrit.</li> <li>H319;</li> <li>Skin Sens. 1, H317</li> </ul>			
CAS: 5444-75-7	2-Ethylhexylbenzoat	10-25%		
	Aquatic Chronic 4, H413			

Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 7 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Hardener)

(Contd. of page 2)

- · After swallowing: Rinse out mouth and then drink plenty of water.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: Not applicable.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Prevent impact and friction.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

- GE



according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 7 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Hardener)

(Contd. of page 3)

## **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Exposure limit values:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Occupational exposure controls:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Body protection: Light weight protective clothing

### **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

**Colour:** According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 5)

## Dr. Schutz®

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 7 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Hardener)

	(Contd. of page 4
<ul> <li>Change in condition</li> <li>Melting point/freezing point:</li> <li>Initial boiling point and boiling range</li> </ul>	Undetermined. : Undetermined.
· Flash point:	111°C (Seta Flash Closed Cup)
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard. Extreme risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure at 20°C:	1hPa
Density at 20°C:     Relative density     Vapour density     Evaporation rate	1.15g/cm <sup>3</sup> Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents:	0.0%
· 9.2 Other information	No further relevant information available.

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity see section "Possibility of hazardous reactions".
- · 10.2 Chemical stability No information available.
- · Conditions to avoid: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.

(Contd. on page 6)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 7 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Hardener)

(Contd. of page 5)

- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow to reach ground water/water course. Do not allow undiluted product or large quantities of it to reach sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

SECTION 14: Transport information

- · 13.1 Waste treatment methods Disposal must be made according to official regulations.
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue				
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances			
15 01 02	plastic packaging			

· Uncleaned packaging:

·IATA

- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION : II Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN3269	
· 14.2 UN proper shipping name		
· ADR	3269 POLYESTER RESIN KIT, ENVIRONMENTALLY HAZARDOUS	
· IMDG	POLYESTER RESIN KIT, MARINE POLLUTANT	

POLYESTER RESIN KIT

(Contd. on page 7)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 7 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Hardener)

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR, IMDG 3 Flammable liquids. · Label ·IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IATA Void · 14.5 Environmental hazards: Product contains environmentally hazardous substances: dibenzoyl peroxide · Marine pollutant: Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Flammable liquids. · EMS Number: F-J,S-R Stowage Category D · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Transport category 2 · Tunnel restriction code D · UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3, **ENVIRONMENTALLY HAZARDOUS** 

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES E1 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB

## Dr. Schutz®

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.08.2017 Version number 7 Revision: 03.02.2017

Identification of the substance/preparation: Dr. Schutz PU Filler / Seamnomor (Hardener)

(Contd. of page 7)

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H241 Heating may cause a fire or explosion.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing SDS: Department for product development
- · Contact: Dr. Reindl

## · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Self-react. E: Self-reactive substances and mixtures - Type E/F

Org. Perox. B: Organic peroxides - Type B

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

· \* Data compared to the previous version altered.

GB