

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Identification of the substance/preparation:** *eukula PU 550 Härter*

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Process category** PROC10 Roller application or brushing

· **Application of the substance / the mixture** Lacquer

· **1.3 Details of the supplier of the safety data sheet**

· **Company/undertaking identification:**

eukula

a Brand of Dr.Schutz GmbH

Holbeinstraße 17

D-53715 Bonn

Phone: +49 (0) 228 / 95352-50

Fax: +49 (0) 228 / 95352-55

info@eukula.com

For the UK:

Dr. Schutz UK Ltd.

Unit 24, Anglo Business Park,

Smeaton Close, Aylesbury Bucks

HP19 8UP

Tel.: 0044 / 1296 437827

Fax: 0044 / 1296 334219

email: steve@dr-schutz.com

· **Further information obtainable from:** Department for product development

· **1.4 Emergency telephone number:**

GBK Gefahrgut Büro GmbH

telephone: +49 (0)6132 84463

(24-Hour-Number)

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



health hazard

Resp. Sens. 1      H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT RE 2      H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4      H332 Harmful if inhaled.

Skin Irrit. 2      H315 Causes skin irritation.

Eye Irrit. 2      H319 Causes serious eye irritation.

(Contd. on page 2)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

**Identification of the substance/preparation:** *eukula PU 550 Härter*

(Contd. of page 1)

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labelling:**

Reaction mass of ethylbenzene and xylene

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidene trimethanol  
m-tolylidene diisocyanateHexamethylene diisocyanate oligomers (uretdione type)  
aromat. Polyisocyanate· **Hazard statements**

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing  
protection.P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with  
water [or shower].P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,  
if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international  
regulations.· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

GB

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

**Identification of the substance/preparation:** *eukula PU 550 Härter*

(Contd. of page 2)

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

#### • Dangerous components:

CAS: 53317-61-6	Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylidene trimethanol ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 103051-64-5	aromat. Polyisocyanate ⚠ Skin Sens. 1, H317	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	10-25%
EC number: 905-588-0	Reaction mass of ethylbenzene and xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	≥10-<20%
CAS: 112-07-2 EINECS: 203-933-3 Index number: 607-038-00-2	2-butoxyethyl acetate ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332	5-10%
CAS: 28182-81-2	Hexamethylene diisocyanate oligomers (uretdione type) ⚠ Acute Tox. 3, H331; ⚠ Skin Sens. 1, H317; STOT SE 3, H335	5-10%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.1-<0.25%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4	m-tolyldiene diisocyanate ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	≥0.1-<1%

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### • General information:

Take affected persons out of danger area and lay down.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### • After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### • After skin contact: Immediately wash with water and soap and rinse thoroughly.

#### • After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### • After swallowing: Rinse out mouth and then drink plenty of water.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

**Identification of the substance/preparation:** *eukula PU 550 Härter*

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**  
Water with full jet  
Not applicable.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.  
Do not inhale gases / fumes / aerosols.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.  
Wear protective equipment. Keep unprotected persons away.  
Follow instructions on the label and in the Technical Product Information Sheet.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Fumes can combine with air to form an explosive mixture.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store only in the original receptacle.  
Provide solvent resistant, sealed floor.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

**Identification of the substance/preparation:** *eukula PU 550 Härter*

(Contd. of page 4)

Store receptacle in a well ventilated area.

· **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

#### · Exposure limit values:

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk
-----	--

#### 112-07-2 2-butoxyethyl acetate

WEL	Short-term value: 332 mg/m <sup>3</sup> , 50 ppm Long-term value: 133 mg/m <sup>3</sup> , 20 ppm Sk
-----	---

#### 128-37-0 Butylated hydroxytoluene

WEL	Long-term value: 10 mg/m <sup>3</sup>
-----	---------------------------------------

#### 26471-62-5 m-tolylidene diisocyanate

WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
-----	---

· **Additional information:** The lists valid during the making were used as basis.

### · 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

**Identification of the substance/preparation:** *eukula PU 550 Härter*

(Contd. of page 5)

· **Eye/face protection**

Tightly sealed goggles

· **Body protection:** Light weight protective clothing**SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· **General Information**

· <b>Physical state</b>	Fluid
· <b>Colour:</b>	Colourless
· <b>Odour:</b>	Specific type
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Boiling point or initial boiling point and boiling range</b>	135°C
· <b>Flammability</b>	Flammable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	1.1 Vol %
· <b>Upper:</b>	10.8 Vol %
· <b>Flash point:</b>	36°C (Seta Flash Closed Cup)
· <b>Ignition temperature:</b>	280°C
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity at 20°C</b>	29 s (DIN 53211/4)
· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure at 20°C:</b>	6.7 hPa
· <b>Density and/or relative density</b>	
· <b>Density at 20°C:</b>	1.06 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

· **9.2 Other information**

· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Solvent separation test:</b>	< 3%
· <b>Solvent content:</b>	
· <b>Organic solvents:</b>	22.5 %
· <b>VOC (EC)</b>	22.5 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.

· **Information with regard to physical hazard classes**

· <b>Explosives</b>	Not applicable
---------------------	----------------

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

**Identification of the substance/preparation:** *eukula PU 550 Härter*

(Contd. of page 6)

· <b>Flammable gases</b>	Not applicable
· <b>Aerosols</b>	Not applicable
· <b>Oxidising gases</b>	Not applicable
· <b>Gases under pressure</b>	Not applicable
· <b>Flammable liquids</b>	Flammable liquid and vapour.
· <b>Flammable solids</b>	Not applicable
· <b>Self-reactive substances and mixtures</b>	Not applicable
· <b>Pyrophoric liquids</b>	Not applicable
· <b>Pyrophoric solids</b>	Not applicable
· <b>Self-heating substances and mixtures</b>	Not applicable
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Not applicable
· <b>Oxidising liquids</b>	Not applicable
· <b>Oxidising solids</b>	Not applicable
· <b>Organic peroxides</b>	Not applicable
· <b>Corrosive to metals</b>	Not applicable
· <b>Desensitised explosives</b>	Not applicable

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** see section "Possibility of hazardous reactions".
- **10.2 Chemical stability** No information available.
- **Conditions to avoid:** No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with alcohols, amines, aqueous acids and alkalis.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

### · LD/LC50 values relevant for classification:

#### 112-07-2 2-butoxyethyl acetate

Oral	LD50	2,400 mg/kg (rat)
Dermal	LD50	1,580 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

### · Endocrine disrupting properties

128-37-0	Butylated hydroxytoluene	List II
----------	--------------------------	---------

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 8)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

**Identification of the substance/preparation:** *eukula PU 550 Härter*


(Contd. of page 7)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN number or ID number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>  | UN1263  |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul>  | 1263 PAINT<br>PAINT   |
| <ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>  | <div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul> |
| <ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   | 3 Flammable liquids.<br>3<br>III  |
| <ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>  | No  |
| <ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul> | Warning: Flammable liquids.<br>30<br>F-E, <u>S-E</u><br>E   |
| <ul style="list-style-type: none"> <li>· <b>14.7 Maritime transport in bulk according to IMO instruments</b></li> </ul>   | Not applicable.   |

(Contd. on page 9)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

**Identification of the substance/preparation:** *eukula PU 550 Härter*

(Contd. of page 8)

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category**

3

· **Tunnel restriction code**

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH204 Contains isocyanates. May produce an allergic reaction.

· **Department issuing SDS:** *eukula*, Department Research & Development

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 14 (replaces version 13)

Revision: 03.08.2021

**Identification of the substance/preparation:** *eukula PU 550 Härter*

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Acute Tox. 2: Acute toxicity – Category 2  
Acute Tox. 3: Acute toxicity – Category 3  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Resp. Sens. 1: Respiratory sensitisation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
Carc. 2: Carcinogenicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB