Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

1 Identification

· **Product identifier**

· **Trade name:** *Dr. Schutz Elastic Filler Komp. A*
· **Application of the substance / the mixture** Sealing
· **Uses advised against** Produkt ist nicht für die private Verwendung bestimmt

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Supplier:
Dr. Schutz GmbH
Holbeinstraße 17
D-53175 Bonn
Tel: +49 228/95 35 2-0
Fax: +49 228/95 35 2-46
E-Mail: export@dr-schutz.com

Import:
Schutz NA LLC
219 Monroe Street
Suite P
19464 Stowe, Pennsylvania
USA
Tel.: +1 (877) 272-4889
Mobile: +1 610-310-2412
E-Mail: sam@dr-schutz.us
Web: www.schutzna.com
· **Information department:** Department for product development
· **Emergency telephone number:**
Dr. Schutz NA,
Contact: Sam Jamison
Tel.: 001/877 2724889
Mo-Fr 8am - 7pm

2 Hazard(s) identification

· **Classification of the substance or mixture**


GHS08 Health hazard

Sensitization - Respiratory 1	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carcinogenicity 2	H351 Suspected of causing cancer.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to organs through prolonged or repeated exposure.


GHS07

Acute Toxicity - Inhalation 4	H332 Harmful if inhaled.
Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Sensitization - Skin 1	H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 1)

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

· **Label elements**
· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Modified methane diisocyanate (MDI)
4,4'-methylenediphenyl diisocyanate
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer
· **Hazard statements**
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
· **Information pertaining to particular dangers for man and environment:**
· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 1
Reactivity = 0
· **HMIS-ratings (scale 0 - 4)**



Health = *2
Fire = 1
Reactivity = 0
· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**		
39420-98-9	Modified methane diisocyanate (MDI)	25-50%
101-68-8	4,4'-methylenediphenyl diisocyanate	10-25%
25686-28-6	Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer	≥20-≤25%

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 2)

108-32-7	propylene carbonate	1-5%

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:** Rinse out mouth and then drink plenty of water.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
· **For safety reasons unsuitable extinguishing agents:** Nicht anwendbar
· **Special hazards arising from the substance or mixture** No further relevant information available.
· **Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.
· **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Not required.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 3)

· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
101-68-8	4,4'-methylenediphenyl diisocyanate	0.15 mg/m3
108-32-7	propylene carbonate	34 mg/m³

· **PAC-2:**		
101-68-8	4,4'-methylenediphenyl diisocyanate	5.0 mg/m3
108-32-7	propylene carbonate	370 mg/m³

· **PAC-3:**		
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m3
108-32-7	propylene carbonate	2,200 mg/m³

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store receptacle in a well ventilated area.
· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

101-68-8 4,4'-methylenediphenyl diisocyanate	
PEL	Ceiling limit value: 0.2 mg/m³, 0.02 ppm
REL	Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min
TLV	Long-term value: 0.051 mg/m³, 0.005 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 4)

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
· **Breathing equipment:**
Not necessary if room is well-ventilated.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
· **Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye protection:**


Tightly sealed goggles

· **Body protection:** Light weight protective clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Fluid
Color:	Yellowish
· **Odor:**	Weak, characteristic
· **Odor threshold:**	Not determined.
· **pH-value:**	Mixture reacts violently with water.
· **Change in condition**	
Melting point/Melting range:	Undetermined.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 5)

Boiling point/Boiling range:	Undetermined.
· **Flash point:**	>200°C (>392°F) (Seta Flash Closed Cup)
· **Flammability:**	Not applicable.
· **Decomposition temperature:**	Not determined.
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	Not determined.
Upper:	Not determined.
· **Vapor pressure:**	Not determined.
· **Density at 20°C (68°F):**	1.115 g/cm³ (9.305 lbs/gal)
· **Relative density**	Not determined.
· **Vapor density**	Not determined.
· **Evaporation rate**	Not determined.
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined.
· **Viscosity:**	
Dynamic at 20°C (68°F):	500-800 mPas
Kinematic:	Not determined.
· **Solvent content:**	
Organic solvents:	4.0 %
VOC content ASTM D3960:	0.00 % 0.0 g/l / 0.00 lb/gal
· **Other information**	No further relevant information available.

10 Stability and reactivity

· **Reactivity** siehe Abschnitt "Möglichkeit gefährlicher Reaktionen"
· **Chemical stability** keine Angaben
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 6)

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
101-68-8 4,4'-methylenediphenyl diisocyanate		
Oral	LD50	2,200 mg/kg (mouse)
108-32-7 propylene carbonate		
Oral	LD50	29,000 mg/kg (rat)

· **Primary irritant effect:**
· **on the skin:** Irritant to skin and mucous membranes.
· **on the eye:** Irritating effect.
· **Sensitization:**
No sensitizing effects known.
Sensitization possible through inhalation.
Sensitization possible through skin contact.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
101-68-8	4,4'-methylenediphenyl diisocyanate	3

· **NTP (National Toxicology Program)**
None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow to reach ground water/water course. Do not allow undiluted product or large quantities of it to reach sewage system.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 7)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**
· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**	
· **DOT, ADR, IMDG, IATA**	Not applicable
· **UN proper shipping name**	
· **DOT, ADR, IMDG, IATA**	Not applicable
· **Transport hazard class(es)**	
· **DOT, ADR, ADN, IMDG, IATA**	
· **Class**	Not applicable
· **Packing group**	
· **DOT, ADR, IMDG, IATA**	Not applicable
· **Environmental hazards:**	Not applicable.
· **Special precautions for user**	Not applicable.
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable.
· **UN "Model Regulation":**	Not applicable

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

101-68-8	4,4'-methylenediphenyl diisocyanate

· **TSCA (Toxic Substances Control Act):**
All components have the value ACTIVE.

· **Hazardous Air Pollutants**

101-68-8	4,4'-methylenediphenyl diisocyanate

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 8)

· **Proposition 65**

· **Chemicals known to cause cancer:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD

· **TLV (Threshold Limit Value)**
None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Modified methane diisocyanate (MDI)
4,4'-methylenediphenyl diisocyanate
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer

· **Hazard statements**
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 9)

P284	[In case of inadequate ventilation] wear respiratory protection.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a poison center/doctor.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Training hints**
As of Aug 24, 2023, adequate training must be provided prior to industrial or commercial use.
· **Recommended restriction of use**
People who suffer from allergies, asthma, chronic or recurring respiratory illnesses should not be deployed in any process using the product.
Only for trade users
Not intended for spraying and industrial processing.

· **Department issuing SDS:** Department for product development
· **Contact:**
· **Date of preparation / last revision** 09/11/2025 / -
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2025 Reviewed on 07/19/2024

Trade name: *Dr. Schutz Elastic Filler Komp. A*

(Contd. of page 10)

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Toxicity - Inhalation 4: Acute toxicity – Category 4
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Sensitization - Respiratory 1: Respiratory sensitisation – Category 1
Sensitization - Skin 1: Skin sensitisation – Category 1
Carcinogenicity 2: Carcinogenicity – Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2