

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

1 Identification

- **Product identifier**

- **Trade name:** *Dr. Schutz Mineral Sealer satin*

- **Application of the substance / the mixture** Coating compound/ Surface coating/ paint

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Supplier:

Dr. Schutz GmbH

Holbeinstraße 17

D-53175 Bonn

Tel: +49 228/95 35 2-0

Fax: +49 228/95 35 2-46

E-Mail: export@dr-schutz.com

Import:

Schutz NA LLC

219 Monroe Street

Suite P

19464 Stowe, Pennsylvania

USA

Tel.: +1 (877) 272-4889

Mobile: +1 610-310-2412

E-Mail: sam@dr-schutz.us

Web: www.schutzna.com

- **Information department:** Department for product development

- **Emergency telephone number:**

Dr. Schutz NA,

Contact: Sam Jamison

Tel.: 001/877 2724889

Mo-Fr 8am - 7pm

2 Hazard(s) identification

- **Classification of the substance or mixture**

The product is not classified, according to the Globally Harmonized System (GHS).

- **Label elements**

- **GHS label elements** Not applicable

- **Hazard pictograms** Not applicable

- **Signal word** Not applicable

- **Hazard statements** Not applicable

- **Information pertaining to particular dangers for man and environment:**

- **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 1

Reactivity = 0

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: *Dr. Schutz Mineral Sealer satin*

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

Health = 0

Fire = 1

Reactivity = 0

· Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable**· vPvB:** Not applicable

3 Composition/information on ingredients

· Chemical characterization: Mixtures**· Description:** Mixture of the substances listed below with nonhazardous additions.**· Dangerous components:** Not applicable

4 First-aid measures

· Description of first aid measures**· General information:**

Immediately remove any clothing soiled by the product.

No special measures required.

· After inhalation: Supply fresh air.**· After skin contact:** Rinse with warm water.**· After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Rinse out mouth and then drink plenty of water.**· Information for doctor:****· Most important symptoms and effects, both acute and delayed** No further relevant information available.**· Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media**· Suitable extinguishing agents:** Use fire fighting measures that suit the environment.**· For safety reasons unsuitable extinguishing agents:** Nicht anwendbar**· Special hazards arising from the substance or mixture** Danger of toxic pyrolysis products.**· Advice for firefighters****· Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: *Dr. Schutz Mineral Sealer satin*

(Contd. of page 2)

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

· **Environmental precautions:**

Prevent from spreading (e.g. by damming-in or oil barriers).

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **Reference to other sections**

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

112945-52-5	Siliciumdioxid, auf chemischem Weg gewonnen	18 mg/m ³
1336-21-6	ammonia	30 ppm
9005-00-9	Polyoxyethylenstearylether	5.7 mg/m ³
67-63-0	propan-2-ol	400 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	360 ppm
50-00-0	formaldehyde	0.90 ppm

· **PAC-2:**

112945-52-5	Siliciumdioxid, auf chemischem Weg gewonnen	100 mg/m ³
1336-21-6	ammonia	160 ppm
9005-00-9	Polyoxyethylenstearylether	63 mg/m ³
67-63-0	propan-2-ol	2000 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	220 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	530 ppm
50-00-0	formaldehyde	14 ppm

· **PAC-3:**

112945-52-5	Siliciumdioxid, auf chemischem Weg gewonnen	630 mg/m ³
1336-21-6	ammonia	1100 ppm
9005-00-9	Polyoxyethylenstearylether	380 mg/m ³
67-63-0	propan-2-ol	12000 ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: *Dr. Schutz Mineral Sealer satin*

(Contd. of page 3)

112-34-5	2-(2-butoxyethoxy)ethanol	1300 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	1600 ppm
50-00-0	formaldehyde	56 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Follow instructions on the label and in the Technical Product Information Sheet.
Avoid contact with the eyes and skin.
Do not inhale gases / fumes / aerosols.
No special measures required.
- **Information about protection against explosions and fires:**
No special precautions are necessary if used correctly.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in unopened original receptacles.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Protect from frost.
Store under lock and key and out of the reach of children.
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Do not eat, drink, smoke or sniff while working.
Be sure to clean skin thoroughly after work and before breaks.
- **Breathing equipment:** Not required
- **Protection of hands:**
Impervious gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: *Dr. Schutz Mineral Sealer satin*

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Where there is a danger of the eyes coming into contact with splashes of liquid (i.e. when refilling larger quantities), safety goggles according to EN 166 (i.e. goggles with side shields) are recommended.

· **Body protection:** Light weight protective clothing

· **Limitation and supervision of exposure into the environment**

Follow instructions for use, dosage and waste disposal.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Color:	Whitish
Odor:	Specific type
Odor threshold:	Not determined

· **pH-value at 20°C (68°F):** 8.5

· **Change in condition**

Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	100°C (212°F)

· **Flash point:** >100°C (>212°F) (Seta Flash Closed Cup)

· **Flammability:** Undetermined

· **Decomposition temperature:** Not determined

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower:	Not determined
--------	----------------

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: *Dr. Schutz Mineral Sealer satin*

(Contd. of page 5)

Upper:	Not determined
· Vapor pressure at 20°C (68°F):	23 hPa (17.3 mm Hg)
· Density at 20°C (68°F):	1.031 g/cm ³ (8.604 lbs/gal)
· Relative density	Not determined
· Vapor density	Not determined
· Evaporation rate	Not determined
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined
· Viscosity:	
Dynamic:	Not determined
Kinematic at 20°C (68°F):	30 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	0.0 %
VOC content ASTM D3960:	0.01 %
	0.1 g/l / 0.00 lb/gal
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** siehe Abschnitt "Möglichkeit gefährlicher Reaktionen"
- **Chemical stability** keine Angaben
- **Thermal decomposition / conditions to be avoided:**
Protect from frost.
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No dangerous reactions known.
- **Hazardous decomposition products:** Danger of toxic pyrolysis products.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

2634-33-5 1,2-benzisothiazol-3(2H)-one

Oral LD50 450 mg/kg (ATE)

Inhalative LC50/4h 0.21 mg/l (ATE)

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: *Dr. Schutz Mineral Sealer satin*

(Contd. of page 6)

- **Primary irritant effect:**

- **on the skin:** No further relevant information available.

- **on the eye:** No further relevant information available.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

67-63-0	propan-2-ol	3
50-00-0	formaldehyde	1

- **NTP (National Toxicology Program)**

50-00-0	formaldehyde	K
---------	--------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

50-00-0	formaldehyde	
---------	--------------	--

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** Undetermined

- **Persistence and degradability**

Elimination of contained polymers is possible through precipitation or flocculation.

The solvent is biodegradable.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** Undetermined

- **Mobility in soil** No further relevant information available.

- **Ecotoxic effects:**

- **Behavior in sewage processing plants:**

Technically correct releases of minimal concentrations to adapted biological sewage plants, will not disturb the biodegradability of activated sludge. Before allowing large quantities to be fed into sewage plants, obtain the approval of the responsible authorities.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable

- **vPvB:** Not applicable

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: *Dr. Schutz Mineral Sealer satin*

(Contd. of page 7)

 · **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Disposal must be made according to official regulations.
- **Uncleaned packagings:**
- **Recommendation:**
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning. Packagings that cannot be cleansed are to be disposed of in the same manner as the product.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|----------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | Not applicable |
| · UN proper shipping name | |
| · DOT, ADR, IMDG, IATA | Not applicable |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | Not applicable |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | Not applicable |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable |
| · UN "Model Regulation": | Not applicable |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

 · **Section 355 (extremely hazardous substances):**

50-00-0 formaldehyde

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: Dr. Schutz Mineral Sealer satin

(Contd. of page 8)

Section 313 (Specific toxic chemical listings):

1336-21-6	ammonia
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol
52-51-7	bronopol (INN)
67-63-0	propan-2-ol
112-34-5	2-(2-butoxyethoxy)ethanol
50-00-0	formaldehyde

TSCA (Toxic Substances Control Act):

7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
77-90-7	Tributyl acetylacrylate	ACTIVE
219756-63-5	Alkylether sulphate 7 EO, sodium salt	ACTIVE
9011-05-6	Polymethylharnstoffharz	ACTIVE
	Polyethersiloxan-Copolymer without labeling	*
1336-21-6	ammonia	ACTIVE
68551-13-3	Alcohols, C12-15, ethoxylated propoxylated	ACTIVE
9005-00-9	Polyoxyethylenstearylether	ACTIVE
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	ACTIVE
2634-33-5	1,2-benzisothiazol-3(2H)-one	ACTIVE
52-51-7	bronopol (INN)	ACTIVE
67-63-0	propan-2-ol	ACTIVE
112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE
556-67-2	octamethylcyclotetrasiloxane	ACTIVE
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	ACTIVE
50-00-0	formaldehyde	ACTIVE

Hazardous Air Pollutants

112-34-5	2-(2-butoxyethoxy)ethanol
50-00-0	formaldehyde

Proposition 65
Chemicals known to cause cancer:

50-00-0	formaldehyde
---------	--------------

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: *Dr. Schutz Mineral Sealer satin*

(Contd. of page 9)

- **Carcinogenicity categories**

- **EPA (Environmental Protection Agency)**

50-00-0	formaldehyde	B1
---------	--------------	----

- **TLV (Threshold Limit Value)**

67-63-0	propan-2-ol	A4
---------	-------------	----

50-00-0	formaldehyde	A2
---------	--------------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

50-00-0	formaldehyde	
---------	--------------	--

- **GHS label elements** Not applicable

- **Hazard pictograms** Not applicable

- **Signal word** Not applicable

- **Hazard statements** Not applicable

- **National regulations:**

- **Other regulations, limitations and prohibitive regulations** Other regulations (EC): Directive 2004/42/EC

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Training hints** ---

- **Recommended restriction of use**

Not intended for spraying and industrial processing.

Only for trade users

People who suffer from allergies, asthma, chronic or recurring respiratory illnesses should not be deployed in any process using the product.

- **Department issuing SDS:** Department for product development

- **Contact:**

- **Date of preparation / last revision** 07/28/2026 / 2

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/28/2026

Reviewed on 07/28/2026

Trade name: *Dr. Schutz Mineral Sealer satin*

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

—US—